

# ACOUSTIC POSITIONING

## AAE MODEL 982 SMART CHARGER



- **Charges all AAE 800 & 900 Series Transponders**
- **Fast charges Simrad RPT Transponders**
- **Also charges Simrad MHT, Sonardyne 7656 and ORE 4330A/4350A/B**
- **Battery fault detect function**
- **Comes with menu driven responder test function**
- **Robust construction**
- **Easy to operate, intuitive, 4 key menu**
- **Switches to trickle charge upon completion of main charge**
- **Complete with easy-read, illuminated LCD display, detachable mains lead and manual**

# TECHNICAL SPECIFICATION

Dimensions :205 mm x 64mm x 190mm

Weight :1.4 kg

Mains Input :115 / 230 vac  $\pm$ 10%

Mains Cable :3 core detachable

Key :+ve key pulse

Fuse Rating :500mA. Quick Blow

Pigtail Lead :VMG-4-F5 (Captive)

Cut-out :Switches to trickle charge if heatsink exceeds 70 C

Compatibility:All AAE 800 & 900 Series Beacons. Simrad MHT316/9, Simrad RPT316/9/324, Sonardyne 7656, ORE4330A & 4350A/B, Responders.

July 2001



Marine House, Marine Park, Gapton Hall Road, Great Yarmouth, NR31 0NL, England  
Tel: + 44 (0) 1493 440355 Fax: + 44 (0) 1493 440720  
[www.appliedacoustics.com](http://www.appliedacoustics.com) email: [general@appliedacoustics.com](mailto:general@appliedacoustics.com)

**Due to continual product improvement these specifications may be subject to change without notice.**