



RUGGED WINDOWS CE GPS HANDHELD FOR ACCURATE MOBILE MAPPING

MobileMapper CE

THE ULTIMATE MOBILE MAPPING PLATFORM

MobileMapper™ CE is the next generation handheld GPS mobile mapping device from Thales Navigation. An open-platform design with embedded Microsoft® Windows® CE .NET, MobileMapper CE supports off-the-shelf Windows CE software for GIS and many other mobile mapping applications.

MobileMapper CE offers must-have features like sub-meter GPS positioning, integrated Bluetooth® wireless technology, removable SD card memory, touch screen, field replaceable all day run-time battery and built-in alphanumeric keypad. Simple, rugged and affordable, MobileMapper CE will accelerate your success without sacrificing performance.

HIGH PERFORMANCE GPS

The simple all-in-one design of MobileMapper CE lets you focus on the task at hand rather than device configuration. With its fully integrated 14-channel GPS receiver, MobileMapper CE offers real-time, sub-meter positioning accuracy through WAAS/EGNOS or external differential corrections. MobileMapper CE GPS technology provides multipath mitigation optimized to overcome environmental challenges in urban canyons and dense foliage.

RUGGED AND WATERPROOF

Designed for extreme outdoor and industrial environments, MobileMapper CE offers performance-focused professionals the ruggedized features they need without sacrificing size, weight or affordability. Fully submersible in 1 meter of water, MobileMapper CE is waterproof in accordance with IEC-529 IPX7. Tested to withstand accidental drops on concrete from 1.5 meters (4.9 ft), and with an operational temperature range from -10°C to +60°C, MobileMapper CE affords even the most demanding users peace of mind in extreme field conditions.



HIGHEST PERFORMANCE-TO-PRICE RATIO IN THE MARKET

MobileMapper CE offers best-in-class performance for the price with user-friendly features and dedicated support from Thales Navigation. With so many integrated features in a highly shock resistant and waterproof device, MobileMapper CE is the next generation mobile mapping tool built to survive the hazards of professional fieldwork. MobileMapper CE - the features and performance you demand at the price you want.

MOBILEMAPPER CE

FEATURES AND SPECIFICATIONS

Standard Features

System

- Microsoft Windows CE .NET 4.2
- ARM9 processor
- 64 MB SDRAM
- Removable SD card memory for data storage
- Full color daylight readable display with touch panel
- Field-worthy, rugged design (IPX7)
- All day removable, rechargeable battery
- Integrated alphanumeric keypad
- Built-in speaker and microphone
- Integrated Bluetooth wireless technology

GPS

- Sub-meter accuracy
- 14 parallel channels with integrated WAAS/EGNOS
- RTCM SC-104 real-time correction support, RTCM version 2.1 (9,2 & 1,2)
- Quadrifilar helix antenna with multipath rejection
- Lemo coaxial external antenna connector

Software

- GPS Utilities - provides initialization and setup, mission planning and configuration of optional beacon differential receiver
- Bluetooth Manager – full-featured Bluetooth connectivity configuration utility
- Microsoft WordPad, Internet Explorer®, Windows Explorer, Terminal, ActiveSync®, Windows Media Player and Inbox
- Microsoft File Viewers: Excel, Word and Image Viewers
- EZ Recorder – sound record and playback program
- Software Development Kit (SDK) and GPS Application Programming Interface (API)

Accessories

- Clip-on I/O module with external power, USB and serial ports
- Universal A/C adapter
- Removable, rechargeable lithium-ion battery
- 32 MB Secure Digital memory card (expandable)
- USB data cable
- Carrying case
- Hand strap
- Stylus pens (2)
- MobileMapper CE companion CD includes supported international language fonts and ActiveSync 3.7.1.
- Getting Started Guide

Optional Features

Accessories

- MobileMapper Beacon – Bluetooth enabled beacon differential correction receiver
- External antenna
- SD cards, 32 MB and 64 MB capacity
- Power cable with cigarette lighter adapter
- 3.7 V lithium-ion rechargeable battery
- Battery charger
- Stylus pen
- Carrying case
- USB data cable

Technical Specifications

Physical Characteristics

Weight

- 0.46 kg (1.01 lb) with battery

Size

- 9 cm x 19.5 cm x 4.6 cm
(3.5 in x 7.7 in x 1.8 in)

Processor

- ARM920T based

Memory

- 64 MB SDRAM, 32 MB SD card (expandable)

User Interface

- Full color advanced TFT liquid crystal display (LCD) with backlight
- 320 x 240 resolution with 262,144 colors
- Resistive touch panel
- Keyboard with backlight: 18 buttons

Audio

- Foil electret condenser microphone and mylar cone speaker with rubber gasket

Power Characteristics

- Battery type: 3.7 V lithium-ion, 3900 mAh
- Battery life: 8 hour run-time with GPS
- External power port for extended operation time

Environmental Characteristics

- Operating Temp: -10°C to 60°C (14°F to 140°F)
- Storage Temp: -20°C to 70°C (-4°F to 158°F)
- Weather: IEC-529 IPX7 Standard (withstands water immersion for > 30 min. at depth of 1 m)
- Shock: 1.5 m (4.9 ft) drop to concrete

Communication Characteristics

- USB host and slave support
- Serial RS232 support
- Bluetooth wireless technology
 - Bluetooth specification: 1.2 compliant
 - Supports point-to-point and point-to-multipoint
 - Profiles: standard serial port, file transfer (OBEX), dial up networking (client support only)

GPS Characteristics

- 14 parallel channels
- Integrated real-time DGPS: WAAS or EGNOS
- Update rate: 1 Hz
- Protocol: NMEA 0183 v 3.0 and MobileMapper Measurements (Thales Navigation format)
- DGPS position accuracy: Sub-meter⁽¹⁾ RMS

Emissions Certification

- Immunity (EN 55022 Class B)
- Susceptibility (EN 50082-1)
- FCC and CE certified

Language Support

- Full Microsoft Windows CE operating system language support - includes Western and Eastern European languages and multibyte languages such as Japanese, Korean and simplified Chinese
- Standard Thales Navigation software user interface available in English, French, German and Spanish

⁽¹⁾ Accuracy assumes open sky environment, #SVs > 5 and PDOP < 4

Thales Navigation, Inc.

Mobile Mapping Contact Information

European Headquarters, Carquefou, France

+33 2 28 09 38 00 • Fax +33 2 28 09 39 39

In Germany +49 81 6564 7930 • Fax +49 81 6564 7950

In Russia +7 095 956 5400 • Fax +7 095 956 5360

In UK +44 870 601 0000 • Fax +44 208 391 1672

In the Netherlands +31 78 61 57 988 • Fax +31 78 61 52 027

Email mobilemappingemea@thalesnavigation.com

Web site www.thalesnavigation.com

Thales Navigation follows a policy of continuous product improvement; specifications and descriptions are thus subject to change without notice. Please contact Thales Navigation for the latest product information.

©2004 Thales Navigation, Inc. All right reserved. MobileMapper is a trademark of Thales Navigation. All other product and brand names are trademarks or registered trademarks of their respective holders. Aerial image courtesy of AirPhotoUSA. Rev (6-30-04) Part # XC20087

THALES