

IronView CW400 Data Collector

Rugged Handheld Device

key features

- IP65 Certified
- Sunlight readable display
- 5-megapixel built-in camera
- Full communication set
- Built-in GNSS receiver

The IronView CW400 is Hemisphere GNSS' next-generation professional grade GNSS data collector. The rugged handheld includes a high-sensitivity GNSS antenna and performs well in challenging environments, such as forests and urban areas.

The integrated 5-megapixel digital camera allows you to capture accurate pictures of any situation in the field. The CW400 is compatible with high-capacity MicroSD cards, ensuring there is enough storage space for large data and faster background maps. Integrated Bluetooth and wireless LAN capabilities enable the CW400 to connect to networks and other devices freely.

The CW400 is the perfect fit for field work. The rugged hand-held is designed with a 3.7" industrial high contrast, sunlight-readable touchscreen display. The CW400 meets IP65 standard, making it both dust and water resistant. Two batteries provide up to 14 hours of use allowing GNSS data collection for a full working day without the need to recharge.



IronView CW400 Data Collector

Physical Specifications

Weight: 483g (including battery)
Size: 192 x 93 x 42mm
Operating Temperature: -30°C to 60°C (-22°F to 140°F)
Storage Temperature: -40°C to 80°C (-40°F to 176°F)
Protection Class: IP65 dust and water resistant
Humidity: 5%-95 %, non-condensing
Vibration: ASAE EP455 Section 5.15.1
Random, MIL- STD-810G, method 514.6E-I
Shock: Withstands 1.2 m drop onto hard surface

System Platform

Operating System: Windows Mobile 6.5
Processor: TI Sitara™ AM335x 1GHz
Memory: 512M
Internal Storage: 8GB
External Storage: Micro SD card up to 32GB
Camera: Internal, autofocus, 5 MP

Interfaces

Display: 3.7inch, Blaview TFT, 480×640VGA
Keypad: Alphanumeric keypad
Dedicated "START" and "CAMERA" key
Programmable short-cut keys (2 on keypad and 1 on left side)
Connectors: Serial port (DB9)
USB OTG 2.0 (Mini AB type) DC in
Communication: Bluetooth 2.1 EDR
WLAN 802.11 a/b/n WCDMA 3.75G
Five Bands UMTS/HSPA+ (WCDMA/FDD) (850/800, 900, 1900 and 2100 MHz), Quad-Band GSM (850/900/1800/1900 MHz)
Other: Micro SIM
Micro SDHC

GNSS

Chipset: uBlox M8T (with raw data output)
Receiver: 72 channels
GPS/QZSS L1 C/A
GLONASS L10F
BeiDou B1
SBAS L1 C/A: WAAS, EGNOS, MSAS, GAGAN
Galileo E1B/C
Update Rate: 1Hz
Position Accuracy: 2.5 m CEP (Autonomous)
2.0 m CEP (SBAS)
Cold Start Time: 30 seconds
Hot Start Time: 1 second
Update Rate: 1Hz

Power supply

Internal Battery: Removable Li-Ion battery
3400mAh 7.2
24.48Wh
AC Power: Input: 100V-240V 50/60Hz
Output: 15V 2A
Operating Time: Up to 10 hours

Authorized Distributor:

Copyright Hemisphere GNSS, Inc. All rights reserved. Specifications subject to change without notice.
Hemisphere GNSS, aRTK, Athena, Atlas, BaseLink, Crescent, Eclipse, SmartLink, SureFix, Tracer, and Vector are trademarks of Hemisphere GNSS, Inc.
Rev. 3/19



Hemisphere GNSS, Inc.
8515 E. Anderson Drive
Scottsdale, AZ, USA 85255

Toll-Free: +1 (855) 203-1770
Phone: +1 (480) 348-6380
Fax: +1 (480) 270-5070
precision@hgnss.com
www.hgnss.com