

Teledyne Odom Hydrographic

# Echotrac MK III

Dual-Frequency Echo Sounder

## The Compact Unit that Does It All

Like to keep your options open? Then Teledyne Odom's ECHOTRAC MKIII is the echo sounder for you! It's the only sounder on the market offering you the choice of either a high-resolution thermal paper recorder or a full-sized color LCD chart in interchangeable module format.

When it comes from Teledyne Odom, you know it's durable, easy to use and backed by the best customer service in the industry. Both high and low channels feature frequency agility, enabling the operator to precisely match the transceiver to almost any existing transducer. This matching ability minimizes near-surface noise caused by transducer ringing while increasing echo return strength. The MKIII is capable of both shallow and deep-water operations, and it features unsurpassed interfacing flexibility with four serial ports and high speed Ethernet capability for maximum efficiency.

More than 30 years of technology enhancements, along with unparalleled performance and precision make TOH sounders the #1 choice for Hydrographic Offices around the world.



### PRODUCT FEATURES

- Interchangeable paper chart or color LCD
- Frequency agile (both channels)
- Internal data storage and playback with color LCD
- Four serial ports and Ethernet interface
- AC/DC power input
- Selectable Receiver bandwidth for shallow/deep water echo sounding
- Silas compatible output for sediment analysis

### Options

- Remote Display
- Side Scan Transducer 200kHz or 340kHz
- Built-in DGPS



# Echotrac MK III

Dual-Frequency Echo Sounder

## TECHNICAL SPECIFICATIONS

|  |  |
|--|--|
| <b>Frequency</b>                           | High band: 100kHz-1MHz<br>Low band: 3.5kHz-50kHz   |
| <b>Output Power</b>                        | High: 100kHz-1kW RMS max 200kHz-900W RMS max, 750kHz-300W RMS max<br>Low: 3.5kHz-2kW RMS max, 50kHz-2kW RMS max  |
| <b>Input Power</b>                         | 110 or 220VAC / 24 VDC 120 watts start/50 watts run  |
| <b>Resolution</b>                          | 0.01m / 0.10 ft.   |
| <b>Accuracy</b>                            | 0.01m / 0.10 ft. +/- 0.1% of depth @ 200kHz<br>0.10m / 0.30 ft. +/- 0.1% of depth @ 33kHz<br>0.18m / 0.60 ft. +/- 0.1% of depth @12kHz (corrected for sound velocity)  |
| <b>Depth Range</b>                         | 0.2-200m / 1.0-600 ft. @ 200kHz<br>0.5-1500m / 1.5-4500 ft. @ 33kHz<br>1.0-4000m / 3.0-13,123 ft. @ 12kHz  |
| <b>Phasing</b>                             | Automatic scale change, 10%, 20%, 30% overlap or manual  |
| <b>Printer</b>                             | High resolution 8 dot/mm (203 dpi); 16 gray shades; 216mm (8.5 in) wide thermal paper or film;<br>External ON/OFF switch; Paper advance control  |
| <b>LCD Display (optional)</b>              | 15 in TFT screen; High-Bright (500 NIT); Internal data storage DSO on 40 GB hard disk;<br>Data transfer via Ethernet interface or USB flash drive; Windows XP Embedded   |
| <b>Paper Speed</b>                         | 1cm/min. (0.5 in/min.) to 22 cm/min. (8.5 in/min.); Auto = one dot row advance for each Ping   |
| <b>Sound Velocity</b>                      | 1370-1700m/s<br>Resolution 1m/s  |
| <b>Transducer Draft Setting</b>            | 0-15m (0-50 ft.)   |
| <b>Depth Display</b>                       | On control PC and LCD display  |
| <b>Clock</b>                               | Internal battery backed time, elapsed time and date clock  |
| <b>Annotation</b>                          | Internal-date, time, optional GPS position from built-in Rx.<br>External-up to 80 ASCII characters from RS232 Serial or Ethernet port  |
| <b>Interfaces</b>                          | 4 X RS232 or 3 X RS232 and 1 X RS422<br>Inputs from external computer, motion sensor<br>Outputs to external computer, remote display<br>Outputs with LCD chart-video out<br>Ethernet interface<br>Heave-TSS1 or sounder sentence   |
| <b>Blanking</b>                            | 0 to full scale  |
| <b>Installation</b>                        | Desktop, optional rack mount or bulkhead mount   |
| <b>Help</b>                                | The function of each parameter and its minimum and maximum values can be printed on the paper chart. The record of settings in tabular format is available on demand, and a continuous printout of parameters is available on thermal paper models. Log files are automatically created by Echotrac Control when that software is used to control the sounder. |
| <b>Environmental Operating Temperature</b> | 0°-50°C, 5-90% relative humidity, non-condensing   |
| <b>Dimensions</b>                          | 450mm (17.7 in) H x 450mm (17.7 in)W x 300mm (12.8 in) D   |
| <b>Weight</b>                              | 16kg (35lbs.)  |
| <b>Options</b>                             | 3.5kHz 4-element sub-bottom array  |

Specifications subject to change without notice.  
© 2018 Teledyne Odom Hydrographic. All rights reserved.