

Eclipse™ P328 OEM Board

Experience Unparalleled Accuracy and Reliability with Multi-Frequency, Multi-GNSS RTK and Onboard Atlas® L-Band

key features

- Multi-Frequency GPS, GLONASS, BeiDou, Galileo, and QZSS
- Long-range RTK baselines up to 50 km with fast acquisition times
- Compatible with many RTK sources including Hemisphere GNSS' ROX format, RTCM, CMR, CMR+
- Mechanically and electrically (pin-for-pin) compatible with many other manufacturers' modules
- Atlas® L-band capable to 4 cm RMS
- Athena™ GNSS engine providing best-in-class RTK performance
- Serial, USB, Ethernet and CAN connectivity for ease of use and integration



Track More Signals for the Most Robust Low-Power Multi-Frequency, Multi-GNSS Solution

Track more signals for unparalleled positioning performance with Hemisphere GNSS' new Eclipse P328 OEM board. The latest technology platform enables simultaneous tracking of all satellite signals including GPS, GLONASS, BeiDou, Galileo, QZSS, and L-band making it the most robust and reliable solution for machine control. The power management system efficiently governs the processor, memory, and ASIC making it ideal for multiple integration applications.

Experience Unparalleled Accuracy and Reliability with Advanced Technology Features

The P328 is the most accurate and reliable OEM module with two new advanced technology features; aRTK™ and Tracer™. Hemisphere's all-new aRTK technology, powered by Atlas, allows the P328 to operate with RTK accuracies when RTK corrections fail. Tracer utilizes specialized algorithms to sustain positioning in the absence of correction data.

Scalable Solutions

With the Eclipse P328, positioning is scalable and field upgradable with all Hemisphere software and service options. Utilize the same centimeter-level accuracy in either single frequency mode, or employ the full performance and fast RTK initialization times over long distances with multi-frequency, multi-constellation GNSS signals. High-accuracy L-band positioning from meter to sub-decimeter levels available via Atlas GNSS correction service.

Ease of Migration

Leverage the industry standard form factor for easy upgradeability from other manufacturers' modules.



precision@hgns.com
www.hgns.com

Eclipse P328 OEM Board

GNSS Sensor Specifications

Receiver Type: Multi-Frequency GPS, GLONASS, BeiDou, Galileo, QZSS, and Atlas
 Signals Received: GPS L1CA/L1P/L1C/L2P/L2C/L5, GLONASS G1/G2, P1/P2, BeiDou B1/B2/B3, GALILEO E1BC/E5a/E5b, QZSS L1CA/L2C/L5/L1C, Atlas
 Channels: 600
 GPS Sensitivity: -142 dBm
 SBAS Tracking: 3-channel, parallel tracking
 Update Rate: 1 Hz standard, 10 Hz, 20 Hz or 50Hz optional (with activation)
 Timing (1PPS) Accuracy: 20 ns
 Cold Start: 60 s typical (no almanac or RTC)
 Warm Start: 30 s typical (almanac and RTC)
 Hot Start: 10 s typical (almanac, RTC and position)
 Antenna Input Impedance: 50 Ω
 Maximum Speed: 1,850 kph (999 kts)
 Maximum Altitude: 18,288 m (60,000 ft)

Accuracy

Position:	RMS (67%)	2DRMS (95%)
Autonomous, no SA: ¹	1.2 m	2.5 m
SBAS: ²	0.3 m	0.6 m
Atlas H10 (L-band): ^{1,3}	0.04 m	0.08 m
Atlas H30 (L-band): ^{1,3}	0.15 m	0.30 m
Atlas Basic (L-band): ^{1,3}	0.50 m	1.0 m
RTK: ¹	8 mm + 1 ppm	15 mm + 2 ppm

L-Band Sensor Specifications

Receiver Type: Single Channel
 Channels: 1525 to 1560 MHz
 Sensitivity: -140 dBm
 Channel Spacing: 5.0 kHz
 Satellite Selection: Manual and Automatic
 Reacquisition Time: 15 seconds (typical)

Communications

Serial Ports: 3 x full-duplex (1 x 3.3V CMOS, 1 x 3.3V CMOS with flow control, 1 x RS-232 with flow control)
 1 x USB Device
 1 x Ethernet 10/100Mbps
 2 x CAN (NMEA2000, ISO 11783)
 3.3V CMOS
 Interface Level: 4800 - 115200
 Baud Rates: Hemisphere GNSS proprietary ROX Format, RTCM v2.3, RTCM v3.2, CMR, CMR+
 Correction I/O Protocol: NMEA 0183, Crescent binary ³
 Data I/O Protocol: 1PPS, CMOS, active high, rising edge
 Timing Output: sync, 10 kΩ, 10 pF load
 CMOS, active low, falling edge sync, 10 kΩ, 10 pF load
 Event Marker Input:

Power

Input Voltage: 3.3 VDC +/- 5%
 Power Consumption: 1.1 W GPS (L1)
 1.8 W GPS (L1/L2) and GLONASS (G1/G2)
 2.9 W All Signals + L-band
 Current Consumption: 0.33 A nominal GPS (L1)
 0.55 A nominal GPS (L1/L2) and GLONASS (G1/G2)
 0.88 A nominal All Signals + L-band
 5 VDC maximum
 Antenna Voltage: Antenna Short Circuit Protection: Yes
 Antenna Gain Input Range: 10 to 40 dB

Environmental

Operating Temperature: -40°C to +85°C (-40°F to +185°F)
 Storage Temperature: -40°C to +85°C (-40°F to +185°F)
 Humidity: 95% non-condensing (when in an enclosure)
 Mechanical Shock: EP455 Section 5.14.1
 Operational (when mounted in an enclosure with screw mounting holes utilized)
 EP455 Section 5.15.1 Random
 CE (IEC 60945 Emissions and Immunity)
 FCC Part 15, Subpart B
 CISPR 22
 Vibration: EMC:

Mechanical

Dimensions: 100 L x 60 W x 10 H (mm)
 3.9 L x 2.4 W x 0.4 (in)
 Weight: 44 g (1.56 oz)
 Status Indications (LED): Power, GNSS lock, Differential lock, DGNSS position
 Power/Data Connector: 24 pin male header 2 mm pitch
 16 pin male header 2 mm pitch
 Antenna Connectors: MMCX, female, straight

1 Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity

2 Depends on multipath environment, number of satellites in view, SBAS coverage, satellite geometry, and ionospheric activity

3 Hemisphere GNSS proprietary

4 With future firmware upgrade and activation

Authorized Distributor:

Copyright Hemisphere GNSS, Inc. All rights reserved. Specifications subject to change without notice.
 Hemisphere GNSS, aRTK, Athena, Atlas, BaseLink, Crescent, Eclipse, SmartLink, SureFix, Tracer, and Vector are trademarks of Hemisphere GNSS, Inc.
 Rev. 04/19



Hemisphere GNSS, Inc.
 8515 E. Anderson Drive
 Scottsdale, AZ, USA 85255

Toll-Free: +1 (855) 203-1770
 Phone: +1 (480) 348-6380
 Fax: +1 (480) 270-5070
 precision@hgns.com
 www.hgns.com