

# Harsh environment, flexible solution

Quality radio modems for  
wireless data communication



## SATEL Proof-R4+

SATEL Proof-R4+ is a heavy-duty receiver radio modem that meets the requirements of machine control and smart farming and marine applications. It is built to last dirt, vibration, sand, dust, liquids and lightning.

SATEL Proof-R4+ consists of an IP69K sealed housing and a receiver only radio module with wide 70 MHz tuning range for frequencies 403 ... 473 MHz.

## GNSS

SATEL's radio modems and modules offer a first-class solution for GNSS, machine control and smart farming. Accuracy, continuity and availability are essential.

Read more: [www.satel.com](http://www.satel.com)

**Mission-Critical Connectivity**

# SATEL

SATEL is one of the world's leading experts and innovators of radio modems for wireless data communication. Our solutions are used in wide range of industrial applications. We are known for our high quality, expertise, service and support.

You can contact us directly or get in touch with your local distributor.

# Heavy-duty solution that meets your needs

SATEL Proof-R4+ is a flexible and cost-effective solution that serves various needs. It has a profound electrical protection; both the power and data lines as well as the antenna interface are surge protected. Because of the IP69K-classification it stands high pressure and hot water. It has additional filtering on GNSS frequencies.

The SATEL Proof-R4+ receiver radio modem is compatible with SATEL-EASy+ / -TR4+ / SATELLINE-EASy / -TR1 based radio modems as well as several other radio protocols.

## SATEL Proof-R4+ technical specifications

Complies with requirements in	EU USA Canada Australia
Frequency range	403 ... 473 MHz
RX Sensitivity	-118 ... -105 dBm
Radio data speed max.	28800 bps
Serial interface	RS-232 (TD, RD lines)
Serial data speed max.	115200 bps
Operating voltage range	+7 ... +27.5 Vdc (-15 % / +20 %)
Power consumption	RX 1.2 W (typical)
Interface connector	Deutsch DT04-6P-CL09
Antenna connector	TNC female
Size H x W x D	174 x 95 x 46 mm
Weight	<500 g
IP classification	IP69K

*Values are subject to change without a notice.*

